

4500 SERIES LED

#ELB(xx)B(x)(xx)(xx)

C L A S S
M O U N T
H E I G H T
C O L O R

CLASS

45=Class 1
42=Class 2

MOUNT

C=Flat/Pipe
M=Magnetic

HEIGHT

Magnetic Mount:
L+=Low, 4" dome
H+=High, 6" dome
Flat/Pipe:
LØ=Low, 4" dome
HØ=High, 6" dome

COLOR

LED COLOR / DOME COLOR

- A** AA=Amber/Amber
- A** AC=Amber/Clear
- W** WA=White/Amber
- B** BB=Blue/Blue
- G** GG=Green/Green
- R** RR=Red/Red
- W** WC=White/Clear
- J** Red/Blue Split (J in low dome only)

4500 ECE65 CERTIFIED

6" Dome - Magnetic Mount
#ELB48BMH+AA Amber
#ELB48BMH+BB Blue
6" Dome - Flat/Pipe Mount
#ELB48BCHØAA Amber
#ELB48BCHØBB Blue



Tech Specs	4500 LED
Input Voltage:	10 - 30 Vdc
Current Draw:	1 amp @ 12 Vdc 0.5 amps @ 24 Vdc
Output:	Amber, Blue, Green, White: 9 watts Red: 6 watts
Technology:	12 Gen3 LEDs
Flash Patterns:	8 Flash Patterns
Mounting:	Permanent or Magnetic Mount
Dimensions:	4" Dome: 4.9" (12 cm) H 6" Dome: 6.8" (17 cm) H 6.34" (16 cm) Base Diameter



Features

- Magnetic or Permanent Mount (5000 not available in Magnetic Mount)
- Two Dome Heights - 4" & 6"
- May be pipe mounted
- Lens with UV inhibitor prevents sun fade
- Optional Branch Guard & Dust Cover (for CA Title 13 compliancy for 3000, 4000 or 4500)

4500 Series LED

- 1300 Lumen LED output
- Rated to last 20,000+ hours
- Heavy duty cast aluminum base
- Same footprint as our 3000 & 4000 for easy upgrade option
- 5 Year Warranty
- Class 1, Class 2 & ECE65 models

3000 Series Strobe

- 10 or 20 watt Strobe models available
- May be ordered as Remote or Self-contained units
- Rugged polycarbonate base
- Advanced circuitry designed tolerate high vibration applications
- 2 Year Warranty (strobe tube 1 year)
- Class 2 rated

4000 Series Economy Strobe

- 20 watt Strobe model available
- Heavy duty cast aluminum base
- Advanced circuitry designed tolerate high vibration applications
- 2 Year Warranty (strobe tube 1 year)
- Class 2 rated

5000 Series Economy Strobe

- 15 watt Strobe model available
- Permanent mount only
- Heavy duty cast aluminum base
- Advanced circuitry designed tolerate high vibration applications
- 1 Year Warranty
- Class 2 rated

3000 SERIES STROBE

#3(xx)(x)(x)(x)(x)

W F H M C
A L E O O
T A I U L
S H H T R

WATTS

3000: ØØ=Remote,
1Ø=10 watt, 2Ø=20 watt
(4000 is 20 watt)

FLASH

3000: Ø=Remote,
7=Double & Quad
(4000 has Double & Quad)

4000 SERIES STROBE

#4227(x)(x)(x)

H M C
E O O
I U L
H T R

HEIGHT

L=Low, 4" dome
H=High, 6" dome

MOUNT

C=Flat/Pipe
M=Magnetic

COLOR

A Amber Lens
B Blue Lens
C Clear Lens (white)
G Green Lens
R Red Lens
J Red/Blue Split
(J in low dome only)



(Strobe Tube 1 Yr.)

(w/ Dust Cover)



3000 195 LB. PULL MAGNETIC MOUNT

6" Dome #3207HM(x)-195
4" Dome #3207LM(x)-195
(x)=A, B or R for Amber, Blue or Red

Tech Specs	3000 Strobe	4000 Strobe
Input Voltage:	10 - 30 Vdc	
Current Draw:	10 watt: 1 amp @ 12 Vdc, 0.5 amp @ 24 Vdc 20 watt: 2 amps @ 12 Vdc, 1 amp @ 24 Vdc	20 watt: 2 amps @ 12.8 Vdc, 1 amp @ 24 Vdc
Output:	10 or 20 watt	20 watt
Technology:	Xenon Helix Strobe Tube	
Flash Patterns:	2 Flash Patterns - Double or Quad (user selectable)	
Mounting:	Permanent or Magnetic Mount (polycarbonate lens & base)	Permanent or Magnetic Mount (polycarbonate lens & aluminum base)
Dimensions:	4" Dome: 4.75" (12 cm) H / 6" Dome: 6.66" (17 cm) H x 6.34" (16 cm) Base Diameter	

#E36ØBG6
6" BRANCH GUARD



#E36ØDC6
6" DUST COVER



Beacon ACCESSORIES

3000, 4000 & 4500 models*

4" Metal Branch Guard #E36ØBG4
6" Metal Branch Guard #E36ØBG6
Clear Dust Cover #E36ØDC6

*Not for use with 5000 Series Beacon.

Tech Specs	5000 Economy
Input Voltage:	10 - 30 Vdc
Current Draw:	1.5 amp @ 12 Vdc 0.75 amp @ 24 Vdc
Output:	15 watts
Technology:	Xenon "U" Strobe Tube
Flash Patterns:	2 User Selectable Flash Patterns: Double & Quad
Mounting:	Permanent Mount only
Dimensions:	5.6" (14 cm) Height x 6.89" (18 cm) Diameter

5000 ECONOMY STROBE

Amber Dome #5157LFC
Clear Dome #5157LFA

